



FOR GOOD REASONS

panDOMO[®] SP-GS

Silk Gloss Sealer

Film forming, waterbased acrylic – wax sealer

Silk gloss matt

Slip resistant

Dirt repellent

Hard-wearing

Trafficable



Reg. No. 37344

Manufacturer
with certified quality system
as per DIN EN ISO 9001

ARDEX GmbH
58430 Witten · P.O. Box 6120
GERMANY
Telephone: +49 (0) 23 02/664-0
Telefax: +49 (0) 23 02/664-437
kundendienst@ardex.de
www.ardex.de

panDOMO® SP-GS

Silk Gloss Sealer

Use:

For the interior.

PANDOMO® SP-GS Silk Gloss Sealer is a protective film for PANDOMO® floor systems which have been treated with PANDOMO® SP-SL Stone oil or with PANDOMO® SP-PS water based PU Sealer.

Floors treated with PANDOMO® SP-SL Stone oil have to be primed with PANDOMO® SP-F Pore filler.

Properties:

- Slip resistant
- protects short time from liquids
- trafficable
- Silk gloss finish

PANDOMO® SP-GS forms a Silk gloss finish on the surface. Colors will be enhanced.

Application:

PANDOMO® SP-GS Silk Gloss Sealer can only be applied onto hardened PANDOMO® SP-F Pore filler (min. 4 hours drying time at + 20°C) or onto absolutely dry PANDOMO® SP-PS sealed areas (min. 12 hours drying time at +20°C). PANDOMO® SP-GS Silk Gloss Sealer has to be applied undiluted and homogeneously thin with lambs skin mop. Do not wipe into already dried product. Avoid puddles.

To be observed:

Do not mix PANDOMO® SP-GS with other maintenance and cleaning liquids. It can also not be used for periodic cleaning.

Do not traffic or wipe the floor when still wet.

Clean tools immediately after use with water.

Fully cured only after drying of the Stone Oil resp. PU Sealer after 5-7 days (depending on climatic conditions).

Periodic cleaning:

For the periodic cleaning use PANDOMO® SP-CR. Remove dirt and dust first with the brush of the vacuum-cleaner. Dilute PANDOMO® SP-CR within the ratio 50 ml and 8 liters of water. Wipe the floor and let it dry. Do not rinse with clean water.

Basic Cleaning:

In case of persistent stains of the floor area which do not disappear during the normal cleaning we would suggest to use PANDOMO® SP-BC Base Cleaner please see technical data sheet.

General:

Avoid heavy traffic during the first days. This will result in a much longer lasting floor. Please observe in case of cleaning with PANDOMO® SP-BC the drying times. Before applying the PANDOMO® SP-SL Stone Oil and PANDOMO® SP-GS Silk Gloss Sealer the floor has to be absolutely dry.

Health and safety/disposal:

Keep out of reach from children

Container and content/dispose according to local/regional/national and international laws.

Technical data according to ARDEX quality standards:

Material requirement:	approx. 40 – 50ml/m ²
Density:	approx. 1,0 g/cm ³
PH-Value:	approx. 8,5
Appearance:	liquid cloudy white
Water solvable:	completely
Application temperature:	approx. + 15 - + 25°C Surface temperature Reduce floor heating or switch off.
Drying time:	Touch dry after approx. 30 minutes. Trafficable after 2 hours. After 3-5 days the areas are fully trafficable. Within this period only clean dry or with clear water. With long temperatures and high RH the drying time can be longer.
Marking acc. GHS/CLP:	None
Marking acc. GGVSEB/ADR:	None
GISCODE:	GE 10
Packaging:	Drum 5 L net
Storage:	cool, but free from frost. Close tightly after usage.
Shelf life:	can be stored for approximately 12 months in dry rooms in unopened packaging.

